


Compressori d'aria con trasmissione a cinghia

Belt driven air compressors



CE

AB 50
AB 100
AB 150
AB 200



	L	P	H
AB 50/245	1010/46.6	360/14	730/27.5
AB 100/245-335	1100/42.9	400/15.6	830/32.4
AB 150/245-335	1360/53	540/21	1060/41.3
AB 200/245-335	1460/56.9	640/24.9	1140/44.5




Type	Volt/Hz	Cod.	Lt.	dB (A)	L _{WA}	Grup./Pump	Cil./St.	/min	C.F.M.	m ³ /h	bar	psi	HP	kW	kW	min-1	Kg	m ³
AB 50-245	230/50/1▲X	1431641000	50	72	95	AB 245	2/1	250	8,8	15	10	145	2	1,5	2	1240	50	0.263
AB 100-245	230/50/1▲X	1432002000	100	72	95	AB 245	2/1	250	8,8	15	10	145	2	1,5	2	1240	62	0.393
AB 150-245	230/50/1▲X	1434002000	150	73	95	AB 245	2/1	250	8,8	15	10	145	2	1,5	2	1240	86	0.831
AB 200-245	230/50/1▲X	1436002000	200	73	95	AB 245	2/1	250	8,8	15	10	145	2	1,5	2	1240	100	1.128
AB 100-335	230/50/1▲X	1432011000	100	76	99	AB 335	2/1	310	11	18,6	10	145	3	2,25	3	1540	64	0.393
AB 150-335	230/50/1▲X	1434011000	150	77	99	AB 335	2/1	310	11	18,6	10	145	3	2,25	3	1540	88	0.831
AB 200-335	230/50/1▲X	1436011000	200	77	99	AB 335	2/1	310	11	18,6	10	145	3	2,25	3	1540	102	1.128



CE

AB 150
AB 200



	L	P	H
AB 150	1360/53.5	540/21	1060/41.3
AB 200	1460/57.5	640/24.9	1140/44.4




Type	Volt/Hz	Cod.	Lt.	dB (A)	L _{WA}	Grup./Pump	Cil./St.	/min	C.F.M.	m ³ /h	bar	psi	HP	kW	kW	min-1	Kg	m ³
AB 150-410	400/50/3■	1464531000	150	76	99	AB 410	2/1	400	14	24	10	145	3	2,25	3	1210	95	0.831
AB 200-410	400/50/3■	1465621000	200	76	99	AB 410	2/1	400	14	24	10	145	3	2,25	3	1210	109	0.895
AB 200-480	400/50/3■	1465040000	200	76	99	AB 450	2/2	480	17	29	10	145	4	3	4	1200	140	0.895
AB 200-510	400/50/3■	1465631000	200	78	99	AB 510	2/1	482	17	29	10	145	4	3	4	1470	125	0.895
AB 200-530	400/50/3■	1465410000	200	71	95	AB 671	2/2	520	18,3	31,2	10	145	4	3	4	800	150	0.895



CE

AB 300




Type	Volt/Hz	Cod.	Lt.	dB (A)	L _{WA}	Grup./Pump	Cil./St.	/min	C.F.M.	m ³ /h	bar	psi	HP	kW	kW	min-1	Kg	m ³
AB 300-480	400/50/3■	1466010000	270	76	99	AB 450	2/2	480	17	29	10	145	4	3	4	1200	173	1.242
AB 300-510	400/50/3■	1466571000	270	78	99	AB 510	2/1	482	17	29	10	145	4	3	4	1470	170	1.242
AB 300-530	400/50/3■	1466440000	270	71	95	AB 671	2/2	520	18,3	31,2	10	145	4	3	4	800	186	1.242
AB 300-550	400/50/3■	1466020000	270	75	99	AB 550	2/2	550	19,4	33	10	145	5,5	4,1	5,5	1400	175	1.242
AB 300-670	400/50/3■	1466420000	270	74	97	AB 671	2/2	650	23	39	10	145	5,5	4,1	5,5	1000	180	1.242
AB 300-850	400/50/3■	1466430000	270	76	99	AB 851	2/2	830	29,3	50	10	145	7,5	5,5	7,5	1280	185	1.242

Compressori d'aria con trasmissione a cinghia

Belt driven air compressors



AB 200 F




CE



Type	Volt/Hz	Cod.	Lt.	dB (A)	LWA	Grup./Pump	Cil./St.	/min	C.F.M.	m ³ /h	bar	psi	HP	kW	kW	min-1	Kg	m ³
AB 200-410 F	400/50/3	1522311000	200	76	99	AB 410	2/1	400	14	24	10	145	3	2,25	3	1210	110	0.895
AB 200-480 F	400/50/3	1522020000	200	76	99	AB 450	2/2	480	17	28,8	10	145	4	3	4	1150	140	0.895
AB 200-510 F	400/50/3	1522321000	200	78	99	AB 510	2/1	482	17	29	10	145	4	3	4	1470	130	0.895
AB 200-530 F	400/50/3	1522200000	200	71	95	AB 671	2/2	520	18,3	31,2	10	145	4	3	4	800	150	0.895



AB 300 F




CE



Type	Volt/Hz	Cod.	Lt.	dB (A)	LWA	Grup./Pump	Cil./St.	/min	C.F.M.	m ³ /h	bar	psi	HP	kW	kW	min-1	Kg	m ³
AB 300-510 F	400/50/3	1523711000	270	78	99	AB 510	2/1	482	17	29	10	145	4	3	4	1470	140	1.242
AB 300-480 F	400/50/3	1523010000	270	76	99	AB 450	2/2	480	17	29	10	145	4	3	4	1200	135	1.242
AB 300-530 F	400/50/3	1523410000	270	71	95	AB 671	2/2	520	18,3	31,2	10	145	4	3	4	800	150	1.242
AB 300-550 F	400/50/3	1523030000	270	75	99	AB 550	2/2	550	19,4	33	10	145	5,5	4,1	5,5	1400	145	1.242
AB 300-670 F	400/50/3	1523390000	270	74	97	AB 671	2/2	650	23	39	10	145	5,5	4,1	5,5	1000	150	1.242
AB 300-850 F	400/50/3	1523400000	270	76	99	AB 851	2/2	830	29,3	50	10	145	7,5	5,5	7,5	1280	152	1.242



AB 500 F




CE



Type	Volt/Hz	Cod.	Lt.	dB (A)	LWA	Grup./Pump	Cil./St.	/min	C.F.M.	m ³ /h	bar	psi	HP	kW	kW	min-1	Kg	m ³
AB 500-550 F	400/50/3	1525000000	500	75	99	AB 550	2/2	550	19,4	33	10	145	5,5	4,1	5,5	1400	240	1.920
AB 500-670 F	400/50/3	1526080000	500	74	97	AB 671	2/2	650	23	39	10	145	5,5	4,1	5,5	1000	253	1.920
AB 500-850 F	400/50/3	1527140000	500	76	99	AB 851	2/2	830	29,3	50	10	145	7,5	5,5	5,5	1280	255	1.920
AB 500-981 F	400/50/3	1531000000	500	78	99	AB 981	2/2	912	32,3	54,7	10	145	10	7,5	10	1280	260	1.920
AB 500-1250 F	400/50/3	1528000000	500	77	99	AB 1000	2/2	1080	38	64,8	10	145	10	7,5	10	1080	270	1.920



ABT 500




CE



Type	Volt/Hz	Cod.	Lt.	dB (A)	LWA	Grup./Pump	Cil./St.	/min	C.F.M.	m ³ /h	bar	psi	HP	kW	kW	min-1	Kg	m ³
ABT 500-960	400/50/3●	1621000000	500	77	99	AB 450	2/2	960	33,9	57,6	10	145	4+4	3+3	4+4	1200	255	1.930
ABT 500-1100 ○	400/50/3●	1622000000	500	77	99	AB 550	2/2	1100	38,8	66	10	145	5,5+5,5	4,1+4,1	5,5+5,5	1400	255	1.930
ABT 500-1350 ○	400/50/3●	1623070000	500	76	99	AB 671	2/2	1300	46	78	10	145	5,5+5,5	4,1+4,1	5,5+5,5	1000	290	1.930
ABT 500-1700 ○	400/50/3●	1624060000	500	78	99	AB 851	2/2	1660	58,6	100	10	145	7,5+7,5	5,5+5,5	7,5+7,5	1280	310	1.930



ABT 900




CE



Type	Volt/Hz	Cod.	Lt.	dB (A)	LWA	Grup./Pump	Cil./St.	/min	C.F.M.	m ³ /h	bar	psi	HP	kW	kW	min-1	Kg	m ³
ABT 900-1700 ○	400/50/3●	1629000000	900	78	99	AB 851	2/2	1660	58,6	100	10	145	7,5+7,5	5,5+5,5	7,5+7,5	1280	445	3.276
ABT 900-1960 ○	400/50/3●	1629030000	900	78	99	AB 981	2/2	1824	64,4	109,4	10	145	10+10	7,5+7,5	10+10	1280	488	3.276



ABV 300



CE



Type	Volt/Hz	Cod.	Lt.	dB (A)	LWA	Grup./Pump	Cil./St.	/min	C.F.M.	m ³ /h	bar	psi	HP	kW	kW	min-1	Kg	m ³
ABV 300-335	230/50/1▲	1529960000	270	77	99	AB 335	2/1	310	11	18,6	10	145	3	2,25	3	1540	120	1.078
ABV 300-480 ○	400/50/3▲	1529550000	270	76	99	AB 450	2/2	480	17	28,8	10	145	4	3	4	1200	155	1.078
ABV 300-550 ○	400/50/3▲	1529570000	270	75	99	AB 550	2/2	550	19,4	33	10	145	5,5	4,1	5,5	1400	160	1.078
ABV 300-670 ○	400/50/3▲	1529640000	270	74	97	AB 671	2/2	650	23	39	10	145	5,5	4,1	5,5	1000	180	1.078
ABV 300-850 ○	400/50/3▲	1529660000	270	76	99	AB 851	2/2	830	29,3	50	10	145	7,5	5,5	7,5	1280	200	1.078

SILVER & CRS ROTARY SCREW AIR COMPRESSOR RANGE

CRSD ROTARY SCREW AIR COMPRESSOR RANGE

CRS 7.5/300



NEW Silver D 10/300



CRSD 15/300



CRSD 20/300



CRS Series

- Encapsulated Air-End ■ Compact Design
- Quiet-Noise Levels, as Low as 68 dB(A)
- Automatic Belt Tensioner ■ Automatic Shut-Off
- External Intake Dust Filter
- Micro -Processor Controlled

Silver Range

- Powerful Heavy Duty Motor
- Encapsulated Air End
- 'Easy Control Unit'
- Reduced Maintenance Costs
- Aesthetic Design

- Encapsulated Air-End ■ Compact Design ■ Quiet-Noise Levels, as Low as 68 dB(A)

- Automatic Belt Tensioner ■ External Intake Dust Filter ■ Automatic Shut-Off

- 1 Micron Dryer Pre-Filter ■ 0.01 Dryer After Filter ■ Dryer By-Pass ■ Automatic Dryer Condensate Valve

- Micro -Processor Controlled

- Easy Access to all Serviceable Parts Along with Screw on Separator Cartridge and Oil Filters, means Shorter Downtimes and Reduced Cost for the user During Scheduled Services.

NEW
NEW

Part Number Description	Motor HP	CFM @ 8 Bar	CFM @ 10 Bar	Air Receiver Litres	Sound Pressure dB(A)	Dimensions L x W x H
Silver 10/300	10.0	33.0	30.2	270	67	1460 x 540 x 1250
Silver D 10/300	10.0	33.0	30.2	270	67	1460 x 540 x 1250

CRS7.5/300	7.5	28.0	24.0	270	67	1840 x 656 x 1539
CRS10/300	10.0	37.5	34.3	270	67	1840 x 656 x 1539
CRS15/300	15.0	56.0	51.2	270	68	1840 x 656 x 1539
CRS20/300	20.0	74.0	65.5	270	69	1840 x 656 x 1539

Part Number Description	Motor HP	CFM @ 8 Bar	CFM @ 10 Bar	Air Receiver Litres	Sound Pressure dB(A)	Dimensions L x W x H
CRSD7.5/300	7.5	28.0	24.0	270	67	1438 x 536 x 1312
CRSD10/300	10.0	37.5	34.3	270	67	1438 x 536 x 1312
CRSD15/300	15.0	56.0	51.2	270	68	1438 x 656 x 1468
CRSD20/300	20.0	74.0	65.5	270	69	1438 x 656 x 1468